














- > Reliable detection of vehicles and persons
- > Works regardless of weather
- > Easy parameterization via Bluetooth app
- > Switching outputs and RS485 communication




TYPE DESCRIPTION

Range	6'000mm (6m)
-------	--------------

GENERAL PROPERTIES

Range	100 ... 6'000 mm		
Detection width	500 ... 1'500 mm per side		
Blind area	200 mm		
Detection zone			
Function frequency	79 GHz		
Detection speed	max 30 Km/h at maximum field size		
Supply voltage	9 ... 24 Vdc		
Power consumption	< 2,5 W		
Output	2x semiconductor output NO and NC (max 150mA @ 24 Vdc)		
Display	1x LED green (Detect), 1x LED red (Power)		
Interfaces	Bluetooth, RS-485		
Working temperature range	-40°C ... +80°C		
Housing protection	IP 65		
Connection cable	1m		
Weight	140g		
Cable assignment	ID	Farbe	Beschreibung
	9-24V	Red	+
	GND	Black	-
	B- / RX	White	RS485 B-
	A+ / TX	Grey	RS485 A+
	NO 1	Blue	NO 1
	NO 1	Green	NO 1
	NC 2	Brown	NC 2
	NC 2	Purple	NC 2
	INPUT	Orange	Spare
	GND	Yellow	Spare



ACCESSORIES

Accessories supplied	<ul style="list-style-type: none"> 1x connection cable 1m 1x counter nut plastic 1x rubber seal 1x metal ring 1x adhesive patch 1x instruction manual
----------------------	---

OTHER ACCESSORIES

Optional accessories	<ul style="list-style-type: none"> ITS-Cable5 ITS-Cable10 ITS-Mount 	<ul style="list-style-type: none"> Connection cable 5m Connection cable 10m Mounting bracket
----------------------	--	---

IMPORTANT NOTE

The assembly and installation instructions must be observed. These are stored in the corresponding operating instructions.

Free **ISensor** app for easy parameterization of the sensor



Perimeter Security Equipment Ltd

Mr. Damian Speer | Managing Director

Email: damian@perimetersecurityequipment.co.uk. - Mobile: +44(0)7949 327 184